

# 2024 Lorain County Fair

## Bone Stock Compact

### ACCEPTABLE CARS:

- Any 1980 and newer FWD cars allowed. 112" max wheelbase. Sub frame cars ONLY, no full frame cars. Max 6 cylinder

### PREPARATION:

- All glass except windshield must be removed. Windshield may remain in car. All plastic molding, mirrors, front and rear bumper covers must be removed.
- Air bags must be unhooked or removed.
- Will allow factory fuel tanks as long as it is factory mounted in front of the rear axle.
- Original gas tank may be removed and replaced with a boat type tank or fuel cell.
- Battery may remain under the hood or may be moved to inside the car and securely fastened.

### EXTERIOR:

- Drivers' door may be welded all the way around with 4" x 1/4" plate. All other doors may have 2 4"x4"x1/4" plates per vertical seam, or you may 9 wire or chain doors, 8 places per door.
- Hoods must have 12"x12" hole cut in center, hood may be wired, chained or. May use 2x2 x1/4 angle iron welded to fender and hood in 2 places per side and bolted. Hood must open for inspection.
- Trunk may be 9 wired or chained in 8 spots or may use 2 4"x4"x1/4" plates per vertical seam. You must cut and 8"x8" hole in trunk for inspection.
- Bumpers Must be stock compact bumper, NO tubing bumpers or chrome bumper.
- You may bolt bumper on with max 1/2" bolts or you may weld bumper all the way around at mounting point. No extra welding on bumper

### CAGE:

- You may run a 4-point cage, max size 6" tubing. It is strongly recommended you at least run a rear seat bar and a drivers door bar. You may have a tank protector must be 4" off all sheet metal and attach to rear seat bar.

### TIRES:

- Any DOT or skid tires on factory wheels, NO Vtreads, solids, studded tires or plated wheels.
- Wheel weights must be removed.
- May have a valve stem protector.

**CALL OR TEXT WITH ANY QUESTIONS**  
**JASON STANFIELD @ 216-308-4896**

