

2024 Street Stock Compact Rules

Front wheel drive cars only 110" max wheel base

Car Preparation

- 1. All glass must be removed you may leave front windshield all loose glass that is broken or that is still around the window seals, head and taillights, light bulbs, etc.) **MUST BE REMOVED** prior to bringing the car to the track.
- 2. Car **MUST BE SWEPT** clean from ALL debris, tools, tires and anything that doesn't belong **MUST BE REMOVED**.
- 3. All exterior (chrome, trim, emblems, plastic grills, door handles, plastic bumper covers, spoilers and anything that's plastic or metal that will break and fall off onto track) **MUST BE REMOVED**.
- 4. All interior (carpet, moldings, seat except driver's seat, head liners, door panels, speakers, etc. and anything flammable) **MUST BE REMOVED**.
- 5. Dashboard is optional.

Cage

- A 4-point cage is allowed 4x4 max tube. Seat bar and door bar may go no farther back than 12" past pillar.
- You may have a gas tank shelf off the seat bar 24" wide max, must be 4" away from all sheet metal.
- Halo bars are permitted no angling of halo bar.
- Front window bar may use 9 wires, chain or 3"x1/4" max strapping must go from roof to top of cowl.

Body/Frame

- Doors may be chained or wired in 8 spots per door 2 strands per spot max, or you may weld doors closed with 3x3 1/4" max strapping 4 plates per door.
- Hood may be chained or wired in 8 spots 2 strands per spot, or you may use 2x2x1/4" angle in 4 spots. And you may use all thread from top of core support to bolt down hood max 5/8 all thread. Hoods must have a 12" hole cut in it.
- Trunk may be chained or wired in 8 spots 2 strands per spot max, or you may use 3"x3"x 1/4" plate 6 plates total. Trunks may be tucked.
- Creasing of the rear quarters is allowed no other creasing will be permitted.
- You may remove front body mount in between frame and k frame.

Tires

- Any tire is permitted except studded tires, Bead locks and plated wheels are not permitted you may have lip protectors and valve stem protectors.

Bumpers

- Any OEM bumper permitted. dec, pimp products or adept bumpers are permitted 10-gauge max only 4 gussets allowed max, no larger than a 4" point. Or you may use 4x4x1/4" tubing. Bumpers can be seam welded. No loaded bumpers.
- Bumper mounting, you may use 1 4"x4"x1/4" plate per frame rail to mount bumper, you may use a 6"x6"x1/4" plate on back of bumper to make a flat mounting surface.
- Rear bumper must be stock and can be welded all the way around Mount point.

Gas tank and battery

- Battery may be moved to inside the car and mounted securely to the floor.
- Fuel cells or steel boat tanks are highly recommended. You may use stock tank if in front of rear axle, Stock tank can not be moved to inside the car.

Suspension

- All suspension parts must remain Stock no adding of any metal. Strut risers are permitted.

Fix-it Plates.

- You are allowed 4 4"x4"x1/4" fix-it plates on fresh and pre-run cars must be a 1" gap in between plates.

Aftermarket parts

- You may use a aftermarket radiator, shifter, switch box, headers and spring risers no other aftermarket parts are permitted.

**Any questions call or text
Jason Stanfield 216-308-4896**